

CHARACTERISTICS	UNIT	TPSK2400
Printing speed	mm/s	100
Printing width	mm	48
Resolution	dot/mm	8
Number of dots	dot	384
Columns	Column	24
Character size	dot*dot	16*24
Character type	-	Windows
Bar code type	-	Interleaved 2/5, EAN 8 & EAN 13, codabar,code 39 & code 128
Paper width	mm	60
Paper roll diameter	mm	102
Paper thickness	g/m <sup>2</sup>	60
Paper loading	-	Clamshell™
Voltage	V	24
Current consumption	A	2.5 (average) - 13 (peak)
Head pulse life	pulse	1*10 <sup>B</sup>
Mechanical reliability	km	50
Dimensions (W*D*H)	mm	102*160*204
Weight	g	1700
Operating temperature	°C	-10 to 50
Operating humidity	%RH	20 to 85
Cutter	-	Yes (automatic by pulling the ticket)
Cutter life	cut	300 k
Presenter	-	Paper chute integrated
Data buffer	kB	2
Interface	-	RS 232 (HE10 10 pin connector)
Driver	-	Windows 98/00/Me/XP
Safety standards	-	UL, CSA, FCC Class A, CE
Sensors	-	Paper out, paper low & door open
Options	-	Power supply, communication cable