

# 54 mm | PCPR

Thermal Printer

## Key features


- Phone card & badge printing
- Cost Effectiveness
- Single or double length ISO format card printing

**NEW**



## Main applications

- Phone cards
- Loyalty cards
- Visitor badges



## TECHNICAL SPECIFICATIONS

| CHARACTERISTICS        | UNIT      | PCPR   |
|------------------------|-----------|--|
| Printing speed         | mm/s      | up to 80   |
| Printing width         | mm        | 48   |
| Resolution             | dots/mm   | 8  |
| Number of dots         | dots      | 384  |
| Columns                | char/line | 24 or 32   |
| Character size         | dot*dot   | 12 x 24 or 16 x 24                                     |
| Default code page      | -         | CP 850   |
| Bar code type          | -         | UPC-A, UPC-E, EAN 13, EAN 8, code 39, I2/5, Code 128   |
| Card width             | mm        | 54 (ISO)   |
| Card length            | mm        | 86 or 172 (ISO)  |
| Card thickness         | µm        | 190  |
| Card loading           | -         | Manual (front side)                                    |
| Voltage                | V         | 24 V or 110/240 with power supply block                |
| Power consumption      | VA        | 55   |
| Head pulse life        | pulse     | 1 x 10 <sup>8</sup>                                    |
| Mechanical reliability | -         | 50 000 single cards and 25 000 double ISO format cards |
| Dimensions (W*D*H)     | mm        | 230 x 115 x 95   |
| Weight                 | g         | 600  |
| Operating temperature  | °C/°F     | 5 to 50/41 to 122                                      |
| Operating humidity     | %RH       | 20 - 85  |
| Data buffer            | Kbytes    | 1  |
| Flash memory           | Kbytes    | 64   |
| Interface              | -         | RS232 and USB  |
| Driver                 | -         | Windows 98/00/XP                                       |
| Emulation              | -         | ESC/POS  |
| Safety standards       | --        | CE / UL / CSA / FCC                                    |

## EXAMPLE OF CODIFICATION

### PCPR2000-E00

60 mm card printer - RS&USB - No cutter - No memory extension - Standard color - European power supply