



The PenPlus II™ is a sturdy and reliable printer, used for a variety of purposes in the European market. There are over 250,000 units presently in use there, and the number keeps growing.

Description

The PenPlus II™ was introduced to the U.S. market in 1991 as a low cost solution for the thousands of small merchants who are still using manual imprinters. The printer has been successful due to its low cost of ownership, ease of operation and remarkably low rate of repair. For merchants who want a small, quick, quiet, low cost printer, PenPlus II™ is the one.



- Noiseless.
- Highly Reliable with a repair rate of less than 1%
- Small footprint saves valuable counterspace
- Produces clean, high resolution images, no ribbon required.
- Quick Printing, 1.75 lines per second.
- Utilizes a high grade of thermal paper for long lasting receipts.
- Automatic Paper Loading button and simple paper path eliminates paper jams.
- Compatible with major POS and personal computer systems.
- Virtually Maintenance Free.
- 13 month warranty.

Technical Specifications

Physical Dimensions

Height: 2.5" (60 mm)
 Width: 7" (180 mm)
 Depth: 6" (150 mm)
 Shipping Weight: 2 lbs. 4 oz. (1 kg)
 Operating Temperature: 40-122°F (5-50°C)

Printing

Type: Thermal Dot Matrix
 Method: Thermal, bi-directional
 Speed: 1.75 lines per second
 Input Voltage: 120V or 220V, 50-60 HZ

Paper

Type: Thermal
 Grade: Appleton
 Width: 4.25" (108 mm)
 Length: 65 ft (19.8 m)

Interface

Serial Port: RS232
 Baud Rate: Dip switch selectable at 300, 1200, 4800, 9600

Accessories

Cables

The PenPlus II™ is available with the following cables:

- PenPlus™ to PC Cable
- PenPlus™ to NBS Cable
- PenPlus™ to VF1 Cable

Optional Accessories

- Custom Cables to Order
- Sub D 25 male to Centronix cable

Included Accessories

- PenPlus™ Power Supply
- PenPlus™ Printer Manual

Quality Thermal Printing has never been more AFFORDABLE!

To order call us at 1-866-922-1003