

## Description

Same features as the PenPlus II™ but can be powered by batteries for additional convenience.



- Noiseless.
- Highly Reliable with a repair rate of less than 1%
- Small footprint saves valuable counterspace
- Produces clean, high resolution images, no ribbon required.
- Quick Printing, 1.75 lines per second.
- Utilizes a high grade of thermal paper for long lasting receipts.
- Automatic Paper Loading button and simple paper path eliminates paper jams.
- Compatible with major POS and personal computer systems.
- Virtually Maintenance Free.
- 13 month warranty.

## Technical Specifications

### Physical Dimensions

Height: 2.5" (60 mm)  
 Width: 7" (180 mm)  
 Depth: 6" (150 mm)  
 Shipping Weight: 2 lbs. 4 oz. (1 kg)  
 Operating Temperature: 40-122°F (5-50°C)

### Printing Type:

Thermal Dot Matrix Serial Port

### Method:

Thermal, bi-directional

### Speed: Power

1.75 lines per second

### Input Voltage:

120V or 220V, 50-60 HZ

### Paper

Type: Thermal  
 Grade: Appleton  
 Width: 4.25" (108 mm)  
 Length: 65 ft (19.8 m)

### Interface

Serial Port RS232  
 Dip switch selectable at 300, 1200, 4800, 9600

### Baud Rate

## Accessories

### Cables

The PenPlus II™ is available with the following cables:

- PenPlus™ to PC Cable
- PenPlus™ to NBS Cable
- PenPlus™ to VF1 Cable

### Optional Accessories

- Custom Cables to Order
- Sub D 25 male to Centronix cable

### Included Accessories

- PenPlus™ Power Supply
- PenPlus™ Printer Manual

Quality Thermal Printing has never been more AFFORDABLE!

To order call us at 1-866-922-1003