

Description

Same features as all the PenPlus™ family of thermal printers but can be linked with any device supporting IRDA communication



- Noiseless.
- Highly Reliable with a repair rate of less than 1%
- Small footprint saves valuable counterspace
- Produces clean, high resolution images, no ribbon required.
- Quick Printing, 1.75 lines per second.
- Utilizes a high grade of thermal paper for long lasting receipts.
- Automatic Paper Loading button and simple paper path eliminates paper jams.
- Compatible with major POS and personal computer systems.
- Virtually Maintenance Free.
- 13 month warranty.

Technical Specifications

Physical Dimensions

Height: 2.5" (60 mm)
 Width: 7" (180 mm)
 Depth: 6" (150 mm)
 Shipping Weight: 2 lbs. 4 oz. (1 kg)
 Operating Temperature: 40-122°F (5-50°C)

Paper
 Type: Thermal
 Grade: Appleton
 Width: 4.25" (108 mm)
 Length: 65 ft (19.8 m)

Printing Type:

Thermal Dot Matrix
 Interface
 Serial Port

RS232
 Dip switch
 selectable at
 300,
 1200,4800,9600

Method:

Thermal, bi-directional
 Baud Rate

Speed:

1.75 lines per second

Power

Input Voltage:

120V or 220V, 50-60 HZ

Accessories

Cables

The PenPlus II™ is available with the following cables:

- PenPlus™ to PC Cable
- PenPlus™ to NBS Cable
- PenPlus™ to VF1 Cable

Optional Accessories

- Custom Cables to Order
- Sub D 25 male to Centronix cable

Included Accessories

- PenPlus™ Power Supply
- PenPlus™ Printer Manual

Quality Thermal Printing has never been more AFFORDABLE!

To order call us at 1-866-922-1003